

**PRODUCT INFORMATION**

# 23" Outdoor E-paper Display

IK09 and IP67 rated outdoor e-paper displays are supplied in a ruggedized enclosure with toughened front glass, designed to be installed within the customer's own structures or to any fixed surface. With wireless, battery and solar capabilities as standard, all models come with optional illumination, interactive functions and text-to-speech modules


**GENERAL**

Dimension (L x H x W)	634 x 276 x 50mm
Weight	10.1 kg (22.2 lb)
Mounting type	Custom Pole / Wall clamp with security fixing
Colour	RAL 9006 Custom colours also available

**DISPLAY**

Display resolution	3200 x 1200 pixels
Active display area	540 x 203 mm
Pigment	Greyscale (16 levels of grey)
Display type	Reflective
Illumination	Embedded LED front illumination, adjustable
Ambient light sensor	Optional

**ENVIRONMENT**

Operating temperature	Greyscale: -20°C to +70°C (-4°F to +158°F)
Protection	IK09 and IP67

**CONNECTIVITY**

Communication	Mobile network / WiFi / Ethernet
Mobile network	3G or optional 4G/LTE
Mobile network antenna	Internal (external antenna optional)
WiFi (optional)	Dual band (2.4/5 GHz) 802.11 ac/b/g/n
WiFi antenna (optional)	External
Ethernet (optional)	10/100/1000 Mbps

**ELECTRICAL**

Power supply	12 V DC (from AC mains via power supply) or 12 V DC solar panel
Power consumption (1 min data update)	50 mA (without illumination) 70 mA (illuminated)
Power consumption (Text-to-speech)	65 mA (without illumination) 85 mA (illuminated)
Power consumption (User interaction)	75 mA (without illumination) 95 mA (illuminated) Support for full shutdown with timer
Power supply connector	Male 5-pin circular waterproof
Ethernet connector	Ethernet circular waterproof

**CERTIFICATIONS**

Certificate of Conformity, Environmental, Electromagnetic Compatibility (EMC), Radio Equipment Directive (RED), Ingress Protection Rating (min IP67), Impact Protection Rating (min IK09).