

PRODUCT INFORMATION

23" Outdoor E-paper Display (Wide)

IP65 rated outdoor e-paper displays are supplied in a ruggedized enclosure with toughened front glass, designed to be installed within the customer's own structures or to any fixed surface. With wireless, battery and solar capabilities as standard, all models come with optional illumination, interactive functions and text-to-speech modules


GENERAL

| | |
|-----------------------|---|
| Dimension (L x H x W) | 635 x 284 x 59mm |
| Weight | 10.1 kg (22.2 lb) |
| Mounting type | Custom Pole / Wall clamp with security fixing |
| Colour | RAL 9006 Custom colours also available |

DISPLAY

| | |
|----------------------|---|
| Display resolution | 3200 x 1200 pixels |
| Active display area | 540 x 203 mm |
| Pigment | Greyscale (16 levels of grey) |
| Display type | Reflective |
| Illumination | Embedded LED front illumination, adjustable |
| Ambient light sensor | Optional |

ENVIRONMENT

| | |
|-----------------------|---|
| Operating temperature | Greyscale: -20°C to +70°C (-4°F to +158°F) |
| Protection | IP65 |

CONNECTIVITY

| | |
|-------------------------|---------------------------------------|
| Communication | Mobile network or WiFi or Ethernet |
| Mobile network | 3G or optional 4G/LTE |
| Mobile network antenna | Internal (external antenna optional) |
| WiFi (optional) | Dual band (2.4/5 GHz) 802.11 ac/b/g/n |
| WiFi antenna (optional) | Internal / external |
| Ethernet (optional) | 10/100/1000 Mbps |

ELECTRICAL

| | |
|---------------------------------------|---|
| Power supply | 12 V DC (from AC mains via power supply) or 12 V DC solar panel |
| Power consumption (1 min data update) | 50 mA (without illumination) 70 mA (illuminated) |
| Power consumption (Text-to-speech) | 65 mA (without illumination) 85 mA (illuminated) |
| Power consumption (User interaction) | 75 mA (without illumination) 95 mA (illuminated) Support for full shutdown with timer |
| Power supply connector | Male 5-pin circular waterproof |
| Ethernet connector | Ethernet circular waterproof |

CERTIFICATIONS

Certificate of Conformity, Environmental, Electromagnetic Compatibility (EMC), Radio Equipment Directive (RED), Ingress Protection Rating (min IP65), Impact Protection Rating (min IK08)