



32" OPEN FRAME E-PAPER DISPLAY (GREYSCALE AND COLOUR)

Ruggedized IP65 open frame e-paper displays are available with wireless and solar capabilities as standard, designed to offer the ultimate flexibility for installation within the customers own street furniture. Available with optional illumination, interactivity and text-to-speech modules.

GENERAL

Dimension (L×H×W)	760 × 460 x 50 mm
Weight	24 kg (52.9 lb)
Mounting type	Embedded (VESA 200 M8)

DISPLAY

Display resolution	RGB 1280 × 720 pixel Greyscale 2560 × 1440 pixels
Active display area	690 × 390 mm
Pigment	RGB (4 bit levels for each RGBW channel) Greyscale (16 levels of grey)
Display type	Reflective
Illumination	Embedded LED front illumination, adjustable
Ambient light sensor	Optional

ENVIRONMENT

Operating temperature	Greyscale: 0°C to +50°C (32°F to +122°F) Black & white: -15°C to +70°C (-5°F to +158°F)
Protection	IP65

CONNECTIVITY

Communication	Mobile network or WiFi or Ethernet
Mobile network	3G or optional 4G/LTE
Mobile network antenna	Internal (external antenna optional)
WiFi (optional)	Dual band (2.4/5 GHz) 802.11 ac/b/g/n
WiFi antenna (optional)	Internal / external
Ethernet (optional)	10/100/1000 Mbps

ELECTRICAL

Power supply	12 V DC (from AC mains via power supply) or 12 V DC solar panel
Power consumption (1 min data update)	50 mA (without illumination) 100 mA (illuminated)
Power consumption (Text-to-speech)	90 mA (without illumination) 140 mA (illuminated)
Power consumption (User interaction)	100 mA (without illumination) 150 mA (illuminated)
	Support for full shutdown with timer
Power supply connector	Male 5-pin circular waterproof
Ethernet connector	Ethernet circular waterproof