



8 Hamburg -Altona

4 min

ARR 18:10
DEP 18:15



ICE 70

| | |
|---------------------|---------------------|
| 18:42 Freiburg | 19:50 Mannheim Hbf |
| 19:10 Baden-Baden | 20:30 Frankfurt Hbf |
| 19:25 Karlsruhe Hbf | 21:15 Fulda |

1st

2nd

A B C D E F

57" OPEN FRAME E-PAPER DISPLAY (WIDE)

Ruggedized IP65 open frame e-paper displays are available with wireless and solar capabilities as standard, designed to offer the ultimate flexibility for installation within the customers own street furniture. Available with optional illumination, interactivity and text-to-speech modules.

GENERAL

| | |
|-------------------|---------------------------|
| Dimension (L×H×W) | 1398 × 460 × 50 mm |
| Weight | 33.8 kg (74.5 lb) |
| Mounting type | Embedded (VESA 2x 200 M8) |

DISPLAY

| | |
|----------------------|---------------------------------------------------------------------------|
| Display resolution | RGB 5120 x 1440 pixels Greyscale 2560 x 720 pixels |
| Active display area | 1380 × 390 mm |
| Pigment | RGB (4 bit levels for each RGBW channel) Greyscale (16 levels of grey) |
| Display type | Reflective |
| Illumination | Embedded LED front illumination, adjustable |
| Ambient light sensor | Optional |

ENVIRONMENT

| | |
|-----------------------|--------------------------------------------------------------------------------------------------|
| Operating temperature | Greyscale: 0°C to +50°C (32°F to +122°F) Black & white: -15°C to +70°C (-5°F to +158°F) |
| Protection | IP65 |

CONNECTIVITY

| | |
|-------------------------|---------------------------------------|
| Communication | Mobile network or WiFi or Ethernet |
| Mobile network | 3G or optional 4G/LTE |
| Mobile network antenna | Internal (external antenna optional) |
| WiFi (optional) | Dual band (2.4/5 GHz) 802.11 ac/b/g/n |
| WiFi antenna (optional) | Internal / external |
| Ethernet (optional) | 10/100/1000 Mbps |

ELECTRICAL

| | |
|---------------------------------------|-----------------------------------------------------------------|
| Power supply | 12 V DC (from AC mains via power supply) or 12 V DC solar panel |
| Power consumption (1 min data update) | 100 mA (without illumination) 200 mA (illuminated) |
| Power consumption (Text-to-speech) | 180 mA (without illumination) 280 mA (illuminated) |
| Power consumption (User interaction) | 200 mA (without illumination) 300 mA (illuminated) |
| | Support for full shutdown with timer |
| Power supply connector | Male 5-pin circular waterproof |
| Ethernet connector | Ethernet circular waterproof |