

GENERAL

Dimensions	345 x 276 x 50 mm
Weight	6.5 kg
Mounting type	Compatible with standard display mounts (VESA 200 x 200 mm)
Enclosure colour	Bezel: RAL 9005 (Jet Black); Interpon 610 – Bismuth (Textured) / Custom Colours

DISPLAY

_		
Gre	vsca	Ie
010	yscu	

Active display area	267 x 200 mm
Display resolution (Pixels)	1600 x 1200
Grey levels	16
Colour:	
Active display area	267 x 200 mm
Display resolution (Pixels)	1600 x 1200
Displayed colour	4096
Illumination (optional)	Embedded LED front illumination, adjustable
Mean time before failure	>12 years (At 20°C and 65% Humidity)

ENVIRONMENT

Operating temp (Greyscale)	-20°C – 70°C
Operating temp (Colour)	-15°C – 65°C

POWER OPTIONS

Solar power	20W or 40W 24Ah or 48Ah
Integrated rechargable battery	-
Long-life battery	LiSoCl2 14.4v 133Ah
Mains power	90-250Vac 50-60hz to 12vdc 5A
Street light power	90-250Vac 50-60hz to 12vdc 24Ah LiFePO
Power over Ethernet (PoE)	IEEE 802.3af standard

CONNECTIVITY OPTIONS

Cellular network	2G, 3G, 4G, LTE
WiFi (optional)	Dual band (2.4/5 GHz) 802.11 ac/b/g/n
Ethernet (optional)	10/100/1000 Mbps
Bluetooth (optional)	Bluetooth 4.1

ACCESSIBILITY

Text-to-speech (optional)	\otimes
External push button (optional)	8
Braille button ID (optional)	8

CERTIFICATIONS

Certificate of Conformity (CE)	8
Certificate of Conformity (UL)	8
IP67 Ingress Protection Rating	8
IK09 Impact Protection Rating	8

MANAGEMENT & CONTROL

Real-time data integration: GTFS, SIRI, API open standards, bespoke

Content management: Fully configurable graphical area, award-winning design system, defined & custom layouts & templates, Paperstore app & widget library

Device control: Set-up, power, connectivity, activity periods, content mode, illumination, text-to-speech, interactive modes

Monitoring & diagnostics: Temperature, humidity, power status, data consumption, movement detection, analytics & reporting

Alarms & notifications: Via text, email or dashboard for various alert conditions

