

28" Outdoor E-paper Display

IK09 and IP67 rated outdoor e-paper displays are supplied in a ruggedized enclosure with toughened front glass, designed to be installed within the customer's own structures or to any fixed surface. With wireless, battery and solar capabilities as standard, all models come with optional illumination, interactive functions and text-to-speech modules

| STATE OF THE PARTY. | 29/06/22 10:13 | | | |
|---------------------|---------------------------|-------------------------------|--|------------------|
| | 28 Clark Road | $^{\$}1$ min | $^{\odot}$ 9 min | |
| | 67 Woodlands | 4 _{min} | 11 7 min | 1 1 |
| | A2 Eastport International | [⊗] 5 _{min} | 20 min | |
| | 19 | | | |
| | 29/06/2 | 22 16:45 | | |
| 28 | Clark Road | | $^{	ext{$^{\odot}$}}$ 1 $_{	ext{min}}$ | $^{\odot}$ 9 min |
| 67 | Woodlands | | 4 min | 1 7 min |
| A2 | Fastport Internationa | al | [⊗] 5 min | 20 min |

GENERAL

| Dimensions | 755 x 262 x 50 mm |
|------------------|---|
| Weight | 10 kg |
| Mounting type | Compatible with standard display mounts (VESA 600 x 200 mm) |
| Enclosure colour | Bezel: RAL 9005 (Jet Black); Interpon 610 – Bismuth (Textured) / Custom Colours |

DISPLAY

Greyscale:

| Active display area | 678 x 185 mm |
|-----------------------------|---|
| Display resolution (Pixels) | 3840 x 1080 |
| Grey levels | 16 |
| Colour: | |
| Active display area | - |
| Display resolution (Pixels) | - |
| Displayed colour | - |
| Illumination (optional) | Embedded LED front illumination, adjustable |
| Mean time before failure | >8 years (At 20°C and 65% Humidity) |
| | |

ENVIRONMENT

| - |
|--------------|
| -20°C – 70°C |
| |

POWER OPTIONS

| Solar power | 20W or 40W 24Ah or 48Ah |
|--------------------------------|---|
| Integrated rechargable battery | - |
| Long-life battery | LiSoCl2 14.4v 133Ah |
| Mains power | 90-250Vac 50-60hz to 12vdc 5A |
| Street light power | 90-250Vac 50-60hz to 12vdc 24Ah LiFePO |
| Power over Ethernet (PoE) | IEEE 802.3af standard |

CONNECTIVITY OPTIONS

| Cellular network | 2G, 3G, 4G, LTE | |
|----------------------|--|--|
| WiFi (optional) | Dual band (2.4/5 GHz) 802.11 ac/b/g/n | |
| Ethernet (optional) | 10/100/1000 Mbps | |
| Bluetooth (optional) | Bluetooth 4.1 | |

ACCESSIBILITY

| Text-to-speech (optional) | \otimes |
|---------------------------------|-----------|
| External push button (optional) | 8 |
| Braille button ID (optional) | 8 |

CERTIFICATIONS

| Certificate of Conformity (CE) | \otimes |
|--------------------------------|-----------|
| Certificate of Conformity (UL) | 8 |
| IP67 Ingress Protection Rating | 8 |
| IK09 Impact Protection Rating | 8 |

MANAGEMENT & CONTROL

Real-time data integration: GTFS, SIRI, API open standards, bespoke

Content management: Fully configurable graphical area, award-winning design system, defined & custom layouts & templates, Paperstore app & widget library

Device control: Set-up, power, connectivity, activity periods, content mode, illumination, text-to-speech, interactive modes

Monitoring & diagnostics: Temperature, humidity, power status, data consumption, movement detection, analytics & reporting

Alarms & notifications: Via text, email or dashboard for various alert conditions

