

### **GENERAL**

Dimensions	957 x 740 x 59 mm
Weight	51 kg
Mounting type	Compatible with standard display mounts (VESA 400 x 400 mm)
Enclosure colour	Interpon 610 – Bismuth (Textured) / Custom Colours

	,
Enclosure colour	Interpon 610 – Bismuth (Textured) / Custom Colours
DISPLAY	
Greyscale:	
Active display area	854 x 637 mm
Display resolution (Pixels)	2880 x 2160
Grey levels	16
Colour:	
Active display area	_
Display resolution (Pixels)	-
Displayed colour	-
Illumination (optional)	Embedded LED front illumination, adjustable
Mean time before failure	>8 years (At 20°C and 65% Humidity)
ENVIRONMENT	
Operating temp (Greyscale)	-20°C – 70°C
Operating temp (Colour)	-
POWER OPTIONS	
Solar power	20W or 40W 24Ah or 48Ah
Integrated rechargable battery	-
Long-life battery	LiSoCl2 14.4v 133Ah
Mains power	90-250Vac 50-60hz to 12vdc 5A

### **CONNECTIVITY OPTIONS**

Cellular network	2G, 3G, 4G, LTE
WiFi (optional)	Dual band (2.4/5 GHz) 802.11 ac/b/g/n
Ethernet (optional)	10/100/1000 Mbps
Bluetooth (optional)	Bluetooth 4.1

# **ACCESSIBILITY**

Text-to-speech (optional)	8
External push button (optional)	8
Braille button ID (optional)	$\otimes$

### **CERTIFICATIONS**

Certificate of Conformity (CE)	8
Certificate of Conformity (UL)	8
IP67 Ingress Protection Rating	8
IK09 Impact Protection Rating	8

## **MANAGEMENT & CONTROL**

Real-time data integration: GTFS, SIRI, API open standards, bespoke

Content management: Fully configurable graphical area, award-winning design system, defined & custom layouts & templates, Paperstore app & widget library

**Device control:** Set-up, power, connectivity, activity periods, content mode, illumination, text-to-speech, interactive modes

Monitoring & diagnostics: Temperature, humidity, power status, data consumption, movement detection, analytics & reporting

Alarms & notifications: Via text, email or dashboard for various alert conditions



Street light power

Power over Ethernet (PoE)

LiFePO

90-250Vac 50-60hz to 12vdc 24Ah

IEEE 802.3af standard